



CHLORINATED RUBBER PAINT

Product Description	Chlorocoat is single pack air drying chlorinated rubber paint. It provides resistances to salt water, aliphatic solvents, acid, alkalis and wide range of chemicals
Recommended Use	Long lasting finished coat in chemicals and fertilizer industry, power plants, breweries, swimming pools, also for marine and industrial environments.
PROPERTIES	
Finish	Glossy
Shade	Any shade as per IS: 5
Standard Coverage	9-10sq.mts/ltr
Specific Gravity	1.0-1.2Kg/ltr
Flash Point	26C
Touch Dry	30 Minutes
Hard Dry	8 Hours
Scratch Hardness(Matt)	1000 gms
DFT	30 Microns
APPLICATION SYSTEM	
Method Of application	Air Spray/Brush
Compatible Primer	Zinc Phis Primer
Recoat Interval	24 Hours
Packing	20 Ltrs
Storage Life	If the material remains unmixed and the container are kept firmly sealed, the contents can be stored up to 6 Months without deterioration

Paletto - A Unit of Polycolours Chemicals PVT LTD

605/3&6, 608/4 part, KINFRA Park, Kusumagiri (PO) Kakkanad, Kochi 682030

Ph: 7034055550 **email:** bindu@paletto.in www.paletto.in